

GettyGuide Production Specifications

2/10/04

Kiosk Products

- SeePoint All In One Kiosk System, 18" / 15" Active Matrix TFT LCD, Surface Acoustic Wave Touch Screen, 256MB SDRAM, 40GB Hard Drive, Intel Pentium III 1.24GHz processor, running Windows 2000.
- MediaMatics Stream Express MPEG-2 Decoder
- Kasenna Media Bridge
- USB IrDA Infrared Adapter

Handheld Products

- Toshiba PocketPC e800 PDA, Intel PXA263 400MHz, 4.0" TFT Transreflective Color display, 128MB RAM, 802.11b, running MS PocketPC 2003
- Toshiba High Capacity Li-Ion Battery Pack for PocketPC e800/e805

Server Products

- **Application Servers:** Sun Fire V480, 4 @ 900MHz, 8GB memory, 4 36GB Hard drives; running Solaris 2.8, Sun Java System Application Server Standard Edition 7
- **Database Server:** Sun Fire V480, 8 @ 750 MHz, 32 GB memory, 12 36 GB Hard drives; running Solaris 2.8, Oracle 8i
- **Location Services Servers:** Sun Fire V120, 1 @ 650MHz, 2GB memory, 2 36GB Hard drives; running Solaris 2.8, Sun Java System Application Server Platform Edition 7, PanGo Networks Proximity Platform
- **Audio Servers:** Sun Fire V120, 1 @ 650MHz, 1 GB memory, 2 36 GB Hard drives; running Solaris 2.8, Sun Java System Web Server 6.1
- **Video Servers:** Sun Netra T1 M105, 1 @ 440MHz, 1GB memory, 2 18GB Hard drives and 2 36GB Hard Drives, Sun Netra ST D130 with 2 36GB Hard drives; running Solaris 2.8, Kasenna MediaBase XMP
- **Cache Server:** Sun Cobalt CacheRaQ 4 Integrated Caching Appliance; running Squid